



CFP Pro[®] 20DS Floor Machine

- Switchable 185/330 rpm dual speed
- All-metal construction
- 1.5 hp DC rectified motor with all-steel triple planetary gear box
- Pad driver included with universal clutch plate
- Easy-to-use, fingertip controls
- Safety lock-out switch

Built with a rugged metal construction and a high-powered 1.5 hp motor, the CFP Pro[®] 20DS delivers Dual Speed rotating action for heavy-duty performance in a wide range of applications. The fingertip controls, safety lock-out switch and accessible cord wrap for the 50 foot safety yellow power cord maximize safety, simplify use and expedite storage of this powerful machine.



Dual speed 185/330 rpm DC motor.



Safety lock-out switch.



Cast aluminum chassis and 66 frame motor.



Foot-activated handle lock.



50 foot safety yellow power cord.

Trusted. Reliable. Efficient.

Clarke[®]

Specifications	CFP Pro® 20DS
Model Number	CLARKE20DS
Deck Size	20 in (50.8 cm)
Pad Driver	19 in (48.3 cm)
Low Speed	185 rpm
High Speed	330 rpm
Motor	DC rectified, 66 frame
Power	110 V, 1.5 hp (1,100 W)
Transmission	Triple planetary, all steel
Sound Level	Low: 65 dB A / High: 68 dB A
Power Cable	50 ft (15.2 m), safety yellow
Wheels	(2) 5 in (12.7 cm) non-marking gray
Amp Draw	12-13 amps
Dimensions (L x W x H)	27 x 15 x 17 in (68.6 x 38 x 43 cm)
Weight	98 lb (44.5 kg)
Ship Weight	112 lb (50.8 kg)

Specifications are subject to change without notice.



Simple

- Easy-to-use fingertip controls
- Universal clutch plate
- Safety lock-out switch

Rugged

- All-steel, triple planetary gear box
- 1.5 hp, 66 frame dual speed DC motor
- All-metal construction
- Designed for heavy, daily use

Affordable

- Two rotating speeds in one machine
- Best value in the industry
- High cleaning productivity rate

Clarke®

9435 Winnetka Avenue North
 Brooklyn Park, MN 55445
 Phone: 800.253.0367
 Fax: 800.825.2753
www.clarkeus.com

240 Superior Boulevard
 Mississauga, Ontario, Canada L5T 2L2
 Phone: 800.668.8400
 Fax: 800.263.5111
www.nilfisk-advance.ca